SEGATRICE A NASTRO PER METALLI FERROSI
BAND SAW FOR FERROUS METALS
BANDSAEGEMASCHINE FÜR EISENMETALLE
SCIE A RUBAN POUR METAUX FERREUX
SIERRA DE CINTA PARA METALES FERROSOS
ЛЕНТОЧНЫЙ РАСПИЛОВОЧНЫЙ СТАНОК ДЛЯ МЕТАЛЛОВ

MANUALE DI ISTRUZIONI PER L'USO - INSTRUCTION MANUAL FOR OPERATION
BETRIEBSANLEITUNG - MANUEL D'INSTRUCTIONS POUR L'EMPLOI
MANUAL DE INSTRUCCIONES DE USO
РУКОВОДСТВО ПО ЭКСПЛУАТАЦИИ И ТЕХОБСЛУЖИВАНИЮ

COSTRUTTORE:
MANUFACTURER:
ERBAUER:
CONSTRUCTEUR:
CONSTRUCTOR:
ИЗГОТОВИТЕЛЬ:

MACC s.r.l. SCHIO (VI) - ITALY

MODELLO:
MODEL:
MODELL:
MODELE:
MODELO:
МОДЕЛЬ:

SPECIAL 280 CSO

MATRICOLA:
SERIAL NUMBER:
KENNNUMMER:
MATRICULE:
MATRICULA:
СЕРИЙНЫЙ НОМЕР:

ANNO DI COSTRUZIONE:
YEAR OF CONSTRUCTION:
BAUJAHR:
ANNEE DE CONSTRUCTION:
AÑO DE COSTRUCCION:
ГОД ИЗГОТОВЛЕНИЯ:

2023

CE

DICHIARAZIONE DI CONFORMITA' 'CE'
CERTIFICATE OF CONFORMITY 'EEC'
KONFORMITÄTSBESCHEINIGUNG 'EWG'
DECLARATION DE CONFORMITE 'CE'
DECLARACION DE CONFORMIDAD 'CE'
ДЕКЛАРАЦИЯ О СООТВЕТСТВИИ 'CE'

MACC Costruzioni Meccaniche s.r.l. - Via Lago di Albano, 10 - 36015 Schio (VI) Italy
Tel.: 0445/575005 Fax: 0445/575006 Web site: www.macc.it E-mail: info@macc.it

- **Dichiara, sotto la propria responsabilità, che la macchina nuova descritta in appresso:**
- **Declares, by its own undertaking, that the new machine described below:**
- **Erklärt auf eigene Verantwortung, daß die nachstehend beschriebene neue Maschine:**
- **Déclare sous sa propre responsabilité, que la machine neuve décrite de suite:**
- **Declara, bajo la propia responsabilidad, que la nueva màquina descripta a continuaciòn:**
- **Заявляет под личную ответственность, что описанная новая машина под названием:**

SEGATRICE A NASTRO PER METALLI
BAND SAW MACHINE FOR METALS
BANDSAEGEMASCHINE FÜR EISENMETALLE
SCIE A RUBAN POUR METAUX
SIERRA DE CINTA PARA METALES
ЛЕНТОЧНЫЙ РАСПИЛОВОЧНЫЙ СТАНОК ДЛЯ МЕТАЛЛОВ

TIPO - TYPE - TYP - TYPE – TIPO - ТИП

SPECIAL 280 CSO

MATRICOLA - SERIAL NUMBER - KENNNUMMER - MATRICULE – MATRICULA - СЕРИЙНЫЙ НОМЕР

_____

ANNO DI COSTRUZIONE – YEAR OF CONSTRUCTION - BAUJAHR – ANNEE DE CONSTRUCTION
AÑO DE COSTRUCCION - ГОД ИЗГОТОВЛЕНИЯ

2023

- E' CONFORME ALLA DIRETTIVA MACCHINE 2006/42/CE, ALLA DIRETTIVA COMPATIBILITA' ELETTROMAGNETICA 2014/30/UE ED ALLA DIRETTIVA BASSA TENSIONE 2014/35/UE.

- IS IN COMPLIANCE WITH THE 2006/42/EEC MACHINERY DIRECTIVE, 2014/30/UE DIRECTIVE ON ELECTROMAGNETIC COMPATIBILITY, 2014/35/UE LOW VOLTAGE DIRECTIVE.

- DEN NORMEN BEZÜGLICH DER MASCHINEN-RICHTLINIE 2006/42/EWG, 2014/30/EWG RICHTLINIE ZUR ELEKTROMAGNETISCHEN KOMPATIBILITÄT, 2014/35/EWG RICHTLINIE FÜR NIEDERSPANNUNG ENTSPRICHT.

- EST CONFORME A LA DIRECTIVE MASCHINES 2006/42/CEE, 2014/30/CEE DIRECTIVE SUR LA COMPATIBILITÉ ÉLECTROMAGNÉTIQUE, 2014/35/CEE DIRECTIVE BASSE TENSION.

- HA SIDO FABRICADA CONFORME A LA DIRECTIVA MÁQUINAS 2006/42/CEE, 2014/30/CEE DIRECTIVA COMPATIBILIDAD ELECTROMAGNÉTICA, 2014/35/CEE DIRECTIVA BAJA TENSIÓN.

- ОТВЕЧАЕТ ТРЕБОВАНИЯМ ДИРЕКТИВЫ ПО МАШИНАМ 2006/42/CE, ДИРЕКТИВЫ ОБ ЭЛЕМКТРОМАГНИТНОЙ СОВМЕСТИМОСТИ 2014/30/CE И ДИРЕКТИВЫ О НИЗКОМ НАПРЯЖЕНИИ 2014/35/CE.

Nome della persona autorizzata a costituire il 'Fascicolo Tecnico' - Name of the person authorized to represent the 'Technical File' - Name der Person, auf die "Technical File" vertreten - Nom de la personne autorisée à représenter le 'dossier technique' Nombre de la persona autorizada para representar a la "Ficha Técnica" - Фамилия, имя лица, уполномоченного составить техническую документацию

Macc Costruzioni Meccaniche s.r.l.
MACC Costruzioni Meccaniche s.r.l. - Via Lago di Albano, 10 – 36015 Schio (VI) Italy Tel.: 0445/575005 Fax: 0445/575006

Nome del Rappresentante Legale - Name of the Legal Representative - Name des Gesetzlichen Vertreters
Nom du Représentant Légal - Apellido del Representante Legal - Фамилия, имя законного представителя:

Zanella Gianfranco
MACC Costruzioni Meccaniche s.r.l. - Via Lago di Albano, 10 – 36015 Schio (VI) Italy Tel.: 0445/575005 Fax: 0445/575006

Firma - Signature - Unterschrift - Signature - Firma - Подпись:

_____ _____ **Schio, 2023**

E' SEVERAMENTE VIETATO UTILIZZARE LA MACCHINA SENZA LIQUIDO DI TAGLIO.

IT IS STRICTLY FORBIDDEN TO USE THE MACHINE WITHOUT CUTTING FLUID.

ES IST STRENG VERBOTEN, DIE MASCHINE OHNE SCHNEIDFLÜSSIGKEIT IN BETRIEB ZU NEHMEN.

IL EST SEVEREMENT INTERDIT D'UTILISER LA MACHINE SANS LIQUIDE DE COUPE.

SE PROHÍBE TERMINANTEMENTE UTILIZAR LA MÁQUINA SIN LÍQUIDO DE CORTE.

É SEVERAMENTE PROIBIDO UTILIZAR A MÁQUINA SEM LÍQUIDO DE CORTE.

Категорчески запрещена эксплуатация машины без смазочно-охлаждающей жидкости



SISTEMA DI MICROLUBRIFICAZIONE: SE INSTALLATO SULLA MACCHINA, È OBBLIGATORIO L'USO DI MASCHERINA PROTETTIVA DELLE VIE AEREE. SI CONSIGLIA DI MANTENERE AREATO IL LOCALE.

MICRO-LUBRICATION SYSTEM: IF INSTALLED ON THE MACHINE, THE USE OF **PPE** (AIRWAYS PROTECTION MASK) IS NECESSARY. KEEP THE PLACE AERATED.

MIKRODOSIERGERÄT: FÜR MASCHINEN MIT MIKRODOSIERGERÄT IST ES STRIKT ERFORDERLICH EINE ATEMMASKE ZUM SCHUTZ DER ATEMWEGE ZU TRAGEN. BITTE DAS GERÄT NUR IN GUT BELÜFTETEN RÄUMEN ANWENDEN.

SYSTÈME DE MICRO-LUBRIFICATION: SI LE SYSTÈME EST INSTALLÉ SUR LA MACHINE, IL EST IMPÉRATIF DE PORTER UN MASQUE DE PROTECTION POUR PROTÉGER LES VOIES RESPIRATOIRES. LES LOCAUX DOIVENT ÉGALEMENT ÊTRE VENTILÉS.

SISTEMA DE MICROLUBRICACIÓN: SI ESTÁ INSTALADO EN LA MÁQUINA, ES OBLIGATORIO EL USO DE UNA MÀSCARA PROTECTORA DE LAS VÍAS RESPIRATORIAS. ES ACONSEJABLE MANTENER LA SALA VENTILADA.

SISTEMA DE MICRO-LUBRIFICAÇÃO: SE INSTALADO NA MÁQUINA, O USO DE UMA MÁSCARA PROTETORA DAS VIAS AÉREAS É OBRIGATÓRIO. É ACONSELHÁVEL MANTER O LOCAL VENTILADO.

СИСТЕМА МИКРОСМАЗКИ: ЕСЛИ СИСТЕМА УСТАНОВЛЕНА, ОБЯЗАТЕЛЬНО ИСПОЛЬЗОВАТЬ ЗАЩИТНУЮ МАСКУ И ПРОВЕТРИВАТЬ ПОМЕЩЕНИЕ.

English



Disposal of Old Electrical & Electronic Equipment (Applicable in the European Union and other European countries with separate collection systems)

This symbol on the product or on its packaging indicates that this product shall not be treated as household waste. Instead it shall be handed over to the applicable collection point for the recycling of electrical and electronic equipment. By ensuring this product is disposed of correctly, you will help prevent potential negative consequences for the environment and human health, which could otherwise be caused by inappropriate waste handling of this product. The recycling of materials will help to conserve natural resources. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

Français



Traitement des appareils électriques et électroniques en fin de vie (Applicable dans les pays de l'Union Européenne et aux autres pays européens disposant de systèmes de collecte sélective)

Ce symbole, apposé sur le produit ou sur son emballage, indique que ce produit ne doit pas être traité avec les déchets ménagers. Il doit être remis à un point de collecte approprié pour le recyclage des équipements électriques et électroniques. En s'assurant que ce produit est bien mis au rebus de manière appropriée, vous aiderez à prévenir les conséquences négatives potentielles pour l'environnement et la santé humaine. Le recyclage des matériaux aidera à conserver les ressources naturelles. Pour toute information supplémentaire au sujet du recyclage de ce produit, vous pouvez contacter votre municipalité, votre déchetterie ou le magasin où vous avez acheté le produit.

Deutsch



Entsorgung von gebrauchten elektrischen und elektronischen Geräten (Anzuwenden in den Ländern der Europäischen Union und anderen europäischen Ländern mit einem separaten Sammelsystem für diese Geräte)

Das Symbol auf dem Produkt oder seiner Verpackung weist darauf hin, dass dieses Produkt nicht als normaler Haushaltsabfall zu behandeln ist, sondern an einer Annahmestelle für das Recycling von elektrischen und elektronischen Geräten abgegeben werden muss. Durch Ihren Beitrag zum korrekten Entsorgen dieses Produkts schützen Sie die Umwelt und die Gesundheit Ihrer Mitmenschen. Umwelt und Gesundheit werden durch falsches Entsorgen gefährdet. Materialrecycling hilft den Verbrauch von Rohstoffen zu verringern. Weitere Informationen über das Recycling dieses Produkts erhalten Sie von Ihrer Gemeinde, den kommunalen Entsorgungsbetrieben oder dem Geschäft, in dem Sie das Produkt gekauft haben.

Español



Tratamiento de los equipos eléctricos y electrónicos al final de su vida útil (Aplicable en la Unión Europea y en países europeos con sistemas de recogida selectiva de residuos)

Este símbolo en su equipo o su embalaje indica que el presente producto no puede ser tratado como residuos domésticos normales, sino que deben entregarse en el correspondiente punto de recogida de equipos eléctricos y electrónicos. Asegurándose de que este producto es desechado correctamente, Ud. está ayudando a prevenir las consecuencias negativas para el medio ambiente y la salud humana que podrían derivarse de la incorrecta manipulación de este producto. El reciclaje de materiales ayuda a conservar las reservas naturales. Para recibir información detallada sobre el reciclaje de este producto, por favor, contacte con su ayuntamiento, su punto de recogida más cercano o el distribuidor donde adquirió el producto.

Nederlands



Verwijdering van Oude Elektrische en Elektronische Apparaten (Toepasbaar in de Europese Unie en andere Europese landen met gescheiden ophaalsystemen)

Het symbool op het product of op de verpakking wijst erop dat dit product niet als huishoudafval mag worden behandeld. Het moet echter naar een plaats worden gebracht waar elektrische en elektronische apparatuur wordt gerecycled. Als u ervoor zorgt dat dit product op de correcte manier wordt verwijderd, voorkomt u mogelijk voor mens en milieu negatieve gevolgen die zich zouden kunnen voordoen in geval van verkeerde afvalbehandeling. De recyclage van materialen draagt bij tot het vrijwaren van natuurlijke bronnen. Voor meer details in verband met het recyclen van dit product, neemt u het best contact op met de gemeentelijke instanties, het bedrijf of de dienst belast met de verwijdering van huishoudafval of de winkel waar u het product hebt gekocht.

Svenska



Omhändertagande av gamla elektriska och elektroniska produkter (Användbar i den Europeiska Unionen och andra Europeiska länder med separata insamlingssystem)

Symbolen på produkten eller emballaget anger att produkten inte får hanteras som hushållsavfall. Den skall i stället lämnas in på uppsamlingsplats för återvinning av el- och elektronikkomponenter. Genom att säkerställa att produkten hanteras på rätt sätt bidrar du till att förebygga eventuellt negativa miljö- och hälsoeffekter som kan uppstå om produkten kasseras som vanligt avfall. Återvinning av material hjälper till att bibehålla naturens resurser. För ytterligare upplysningar om återvinning bör du kontakta lokala myndigheter eller sophämtningstjänst eller affären där du köpte varan.

Italiano



Trattamento del dispositivo elettrico od elettronico a fine vita (Applicabile in tutti i paesi dell'Unione Europea e in quelli con sistema di raccolta differenziata)

Questo simbolo sul prodotto o sulla confezione indica che il prodotto non deve essere considerato come un normale rifiuto domestico, ma deve invece essere consegnato ad un punto di raccolta appropriato per il riciclo di apparecchi elettrici ed elettronici. Assicurandovi che questo prodotto sia smaltito correttamente, voi contribuirete a prevenire potenziali conseguenze negative per l'ambiente e per la salute che potrebbero altrimenti essere causate dal suo smaltimento inadeguato. Il riciclaggio dei materiali aiuta a conservare le risorse naturali. Per informazioni più dettagliate circa il riciclaggio di questo prodotto, potete contattare l'ufficio comunale, il servizio locale di smaltimento rifiuti oppure il negozio dove l'avete acquistato.

Język polski



Pozbycie się Zużytego Sprzętu (Stosowane w krajach Unii Europejskiej i w pozostałych krajach europejskich mających własne systemy zbiórki)

Taki symbol na produkcie lub jego opakowaniu oznacza, że produkt nie może być traktowany jako odpad komunalny, lecz powinno się go dostarczyć do odpowiedniego punktu zbiórki sprzętu elektrycznego i elektronicznego, w celu recyklingu. Poprzez upewnię się, że dyspozycja dotycząca produktu jest poprawna, zapobiega się potencjalnym negatywnym wpływom na środowisko oraz zdrowie ludzi, jakie mogłyby wystąpić w przypadku niewłaściwego postępowania. Recykling materiałów pomoże w ochronie naturalnych źródeł. W celu uzyskania bardziej szczegółowych informacji na temat recyklingu tego produktu, należy skontaktować się z naszym lokalnym biurem, ze służbami oczyszczania miasta lub ze sklepem, w którym zakupiony został ten produkt.

Norsk



Avhending av gamle elektriske og elektroniske apparater (gjelder i EU og andre europeiske land med separat innsamlingssystem)

Dette symbolet på produktet eller innpakningen indikerer at dette produktet ikke må håndteres som husholdningsavfall. I stedet skal det leveres inn til spesielt innsamlingspunkt for gjenvinning av det elektriske og elektroniske utstyret. Ved å sørge for at dette produktet avhendes på korrekt måte, vil du hjelpe til med å forhindre potensielle negative påvirkninger på miljøet og helse, som ellers kan være resultatet av feilaktig avfallshåndtering av dette produktet. Gjenvinning av disse materialene vil hjelpe til med å ta vare på våre naturressurser. For mer informasjon om gjenvinning av dette produktet, kan du kontakte lokale myndigheter.

Magyarul



Feleslegessé vált elektromos és elektronikus készülékek hulladékként való eltávolítása (Használható az Európai Unió és egyéb európai országok szelektív hulladékgyűjtési rendszereiben)

Ez a szimbólum a készüléken vagy a csomagolásán azt jelzi, hogy a terméket ne kezelje háztartási hulladékként. Kérjük, hogy az elektromos és elektronikai hulladék gyűjtésére kijelölt gyűjtőhelyen adja le. A feleslegessé vált termékének helyes kezelésével segít megelőzni a környezet és az emberi egészség károsodását, mely bekövetkezhetne, ha nem követi a hulladék kezelés helyes módját. Az anyagok, újrahasznosítása segít a természeti erőforrások megőrzésében. A termék újrahasznosítása érdekében további információért forduljon a lakhelyén az illetékesekhez, a helyi hulladékgyűjtő szolgáltatóhoz vagy ahhoz az üzlethez, ahol a terméket megvásárolta.

Česky



Nakládání s nepotřebným elektrickým a elektronickým zařízením (platné v Evropské unii a dalších evropských státech uplatňujících oddělený systém sběru)

Tento symbol umístěný na výrobku nebo jeho balení upozorňuje, že s výrobkem po ukončení jeho životnosti by nemělo být nakládáno jako s běžným odpadem z domácnosti. Místo toho by měl být odložen do sběrného místa, určeného k recyklaci elektronických výrobků a zařízení. Dodržením této instrukce zabráníte negativním dopadům na životní prostředí a zdraví lidí, které naopak může být ohroženo nesprávným nakladním s výrobkem při jeho likvidaci. Recyklováním materiálů, z nichž je vyroben, pomůžete zachovat přírodní zdroje. Pro získání dalších informací o recyklaci tohoto výrobku kontaktujte, prosím, místní orgány státní správy, místní firmu zabezpečující likvidaci a sběr odpadů nebo prodejnu, v níž jste výrobek zakoupili.

Slovensky



Likvidácia starých elektrických a elektronických zariadení (Platí v Európskej únii a ostatných európskych krajinách so zavedeným separovaným zberom)

Tento symbol na výrobku alebo obale znamená, že s výrobkom nemôže byť nakladané ako s domovým odpadom. Miesto toho je potrebné ho doručiť do vyhradeného zberného miesta na recykláciu elektrozariadení. Tým, že zaistíte správne zneškodnenie, pomôžete zabrániť potencionálnemu negatívnemu vplyvu na životné prostredie a ľudské zdravie, ktoré by v opačnom prípade hrozil pri nesprávnom nakladaní s týmto výrobkom. Recyklácia materiálov pomáha uchovávať prírodné zdroje. Pre získanie ďalších podrobných informácií o recyklácii tohoto výrobku kontaktujte prosím váš miestny alebo obecný úrad, miestnu službu pre zber domového odpadu alebo predajňu, kde ste výrobok zakúpili.

Türkçe



Eski Elektrikli & Elektronik Ekipmanların Atılması (Avrupa Birliği'nde ve ayrı toplama sistemlerine sahip diğer Avrupa ülkelerinde uygulanır)

Ürün veya ambalajı üzerinde bulunan bu sembol, bu ürünün bir ev atigi olarak muamele görmemesi gerektigini gösterir. Bunun yerine, elektrikli ve elektronik ekipmanların geri dönüsümü için mevcut olan uygun toplama noktasina teslim edilmelidir. Bu ürünün dogru sekilde atilmasini saglayarak, bu ürüne yanlis müdahale edilmesi sonucunda ortaya çikabilecek ve çevre ile insan sagligi üzerinde olumsuz etkide bulunabilecek durumlarin önlemesine yardimci olmus olursunuz. Malzemelerin geri dönüsümü, dogal kaynaklari korumamiza yardimci olacaktir. Bu ürünün geri dönüsümüyle ilgili daha fazla bilgi için, lütfen sehrinizde bulunan yerel ofisle, evsel atiklar toplama servisinizle veya bu ürünü satin aldiginiz magazayla temasa geçin.

Slovensko



Oddaja stare električne in elektronske opreme (veljavno v evropski uniji in ostalih evropskih državah s sistemom zbiranja ločenih odpadkov)

Če se na izdelku ali na njegovi embalaži nahaja ta simbol, pomeni, da z izdelkom ne smete ravnati enako kot z drugimi gospodinjskimi odpadki. Morate ga oddati na ustrezno zbirno mesto za recikliranje električne in elektronske opreme. S pravilno oddajo tega izdelka boste pomagali preprečiti negativne posledice na okolje in zdravje ljudi, do katerih bi prišlo v primeru neustreznega ravnanja ob odstranitvi tega izdelka. Recikliranje materiala bo pripomoglo k ohranjevanju naravnih virov. Podrobnejše informacije o recikliranju tega izdelka lahko dobite pri lokalni mestni upravi, službi oddajanja gospodinjskih odpadkov ali v trgovini, kjer ste izdelek kupili. Odpadno električno in elektronsko opremo lahko oddate brezplačno tudi distributerju neposredno ob dobavi električne oz. elektronske opreme.

Русский



Утилизация электрического и электронного оборудования (директива применяется в странах Евросоюза и других европейских странах, где действуют системы раздельного сбора отходов)

Данный знак на устройстве или его упаковке обозначает, что данное устройство нельзя утилизировать вместе с прочими бытовыми отходами. Его следует сдать в соответствующий приемный пункт переработки электрического и электронного оборудования. Неправильная утилизация данного изделия может привести к потенциально негативному влиянию на окружающую среду и здоровье людей, поэтому для предотвращения подобных последствий необходимо выполнять специальные требования по утилизации этого изделя. Переработка данных материалов поможет сохранить природные ресурсы. Для получения более подробной информации о переработке этого изделия обратитесь в местные органы городского управления, службу сбора бытовых отходов или в магазин, где было приобретено изделие.

Suomi



Käytöstä poistetun sähkö- ja elektroniikkalaitteen hävitys (Euroopan Unioni ja muiden Euroopan maiden keräysjärjestelmät)

Symboli, joka on merkitty Tuotteeseen tai sen pakkaukseen, osoittaa, että tätä tuotetta ei saa käsitellä talousjätteenä. Tuote on sen sijaan luovutettava sopivaan sähkö-ja elektroniikkalaitteiden kierrätyksestä huolehtivaan keräyspisteeseen. Tämän tuotteen asianmukaisen hävittämisen varmistamisella autetaan estämään sen mahdolliset ympäristöön ja terveyteen kohdistuvat haittavaikutukset, joita voi aiheutua muussa tapauksessa tämän tuotteen epäasianmukaisesta jätekäsittelystä. Materiaalien kierrätys säästää luonnonvaroja. Tarkempia tietoja tämän tuotteen kierrättämisestä saa paikallisesta kunnantoimistosta.

Dansk



Bortskaffelse af elektrisk og elektronisk udstyr (gælder i EU og andre europæiske lande med egne indsamlingssystemer)

Hvis dette symbol findes på produktet eller på emballagen betyder det, at det pågældende produkt ikke må bortskaffes som almindeligt husholdningsaffald. Du skal i stedet aflevere det på et indsamlingssted, så det elektriske og elektroniske udstyr kan blive genbrugt. Når du bortskaffer produktet korrekt, hjælper du med at forhindre de mulige negative påvirkninger af miljøet eller sundheden, der kan opstå, hvis produktet bortskaffes på upassende vis. Genbrug af materialer er med at bevare naturens ressourcer. Yderligere oplysninger om genbrug af produktet fås på kommunen, på genbrugscentralen eller i den butik, hvor du købte produktet.

Português



Tratamento de Equipamentos Eléctricos e Electrónicos no final da sua vida útil (Aplicável na União Europeia e em países Europeus com sistemas de recolha selectiva de resíduos)

Este símbolo, colocado no produto ou na sua embalagem, indica que este não deve ser tratado como resíduo urbano indiferenciado. Deve sim ser colocado num ponto de recolha destinado a resíduos de equipamentos eléctricos e electrónicos. Assegurando-se que este produto é correctamente depositado, irá prevenir potenciais consequências negativas para o ambiente bem como para a saúde, que de outra forma poderiam ocorrer pelo mau manuseamento destes produtos. A reciclagem dos materiais contribuirá para a conservação dos recursos naturais. Para obter informação mais detalhada sobre a reciclagem deste produto, por favor contacte o município onde reside, os serviços de recolha de resíduos da sua área ou a loja onde adquiriu o produto.

Ελληνικά



Αποκομιδή Παλαιού Ηλεκτρικού & Ηλεκτρονικού Εξοπλισμού(Ισχύει στην Ευρωπαϊκή Ένωση και άλλες Ευρωπαϊκές χώρες με ξεχωριστά συστήματα περισυλλογής)

Το σύμβολο αυτό επάνω στο προϊόν ή στη συσκευασία του σημαίνει ότι το προϊόν δεν πρέπει να πεταχτεί μαζί με τα οικιακά απορρίμματα αλλά πρέπει να παραδοθεί σε ένα κατάλληλο σημείο συλλογής ηλεκτρολογικού και ηλεκτρονικού υλικού προς ανακύκλωση. Με το να βεβαιωθείτε ότι το προϊόν πετάχτηκε σωστά, βοηθάτε στην πρόληψη πιθανών αρνητικών επιπτώσεων στο περιβάλλον και την υγεία. Η ανακύκλωση των υλικών θα βοηθήσει στην εξοικονόμηση φυσικών πόρων. Για περισσότερες πληροφορίες σχετικά με την ανακύκλωση αυτού του προϊόντος, παρακαλούμε επικοινωνήστε με τις υπηρεσίες καθαριότητας του δήμου σας ή το κατάστημα όπου αγοράσατε το προϊόν.

1. INTRODUCTION

This operation instruction manual conforms to the requirements of the 2006/42/EEC Machine Directives and subsequent amendments .
In the light of this , special attention has been given to safety aspects and accident prevention in the work-place for each stage in the machine's "life" . Information which could be of particular assistance to the operator has been highlighted .
The "Operating instructions" are an integral part of the machine and should be consulted before , during and after the start up of the machine and whenever else required . The content of these instructions should always be carefully observed .
The observance of the above is the only way to achieve the two fundamental aims of this manual :

- **Optimization of machine performance**
- **Prevent damage to the machine and injury to the operator**

The index of the chapters and the index of the drawings , diagrams and tables is contained in chapter 3 and can be used to help the location of specific information .

CAUTION : BEFORE INSTALLING THE MACHINE , READ THE OPERATING INSTRUCTIONS CAREFULLY

2. INFORMATION ABOUT MAINTENANCE ASSISTANCE

2.1 GUARANTEE

- MACC S.r.l. products are guaranteed against material and manufacturing defects for a period of 12 months from the date of delivery or , if the machine is installed by MACC employees , from the date of machine start up .
- The buyer is only entitled to the replacement of parts which are acknowledged as faulty : carriage and packing are at the buyer's expense . In the event of the above , the following information should be supplied :

1. Date and number of purchasing document
2. Machine model
3. Serial number
4. Code of any relevant drawings

- Requests for compensation for the inactivity of the machine will not be accepted .
- The guarantee does not cover uses which are not in line with these operating instructions which are an integral part of the machine . Nor is maintenance covered if the instructions supplied are not observed .
- The guarantee will not cover machines which have undergone unauthorized modifications .
- Modification or tampering with the safety devices is strictly forbidden .

3. INDEX

3.1 INDEX OF CHAPTERS

Chap. 1 Introduction
Chap. 2 Information about maintenance assistance
Chap. 3 Index of chapters , drawings , diagrams and tables
Chap. 4 Description of the machine
Safety standards complied with during the design and construction of the machine
Description of the machine and its components
Intended and unsuitable uses of the machine
Chap. 5 Main technical data
Chap. 6 Handling and transportation
Chap. 7 Installation
Chap. 8 Start up and operation
Devices and their location
Tools supplied
Operation
Special safety checks
General safety rules
Measures to prevent residual risks
Safety , Guidance , Notice Labels on the Machine
Chap. 9 Maintenance and repairs
General safety measures
Routine checks and maintenance
Description of routine maintenance
Chap. 10 Information regarding environmental noise
Chap. 11 Laying off – Demolition
Chap. 12 List of spare parts

3.2 INDEX OF DRAWINGS , DIAGRAMS AND TABLES

ENCL. TYPE	DESCRIPTION	ENCL. No.	CHAP.
Table	**Cutting capacity - Selection of blade - Cutting speeds**	**1**	**8.3**
Drawings	**Handling and transportation - Installation plan**	**2**	**6/7A/7B/8.1/9.3**
Drawings	**Blade guides - Blade guide bearings - Vice block**	**3**	**7C/8.3/9.3**
Drawings	**Vice block – Tensioning**	**4**	**8.3/9.3**
Drawings	**Rotation block - Motor - Machine exploded view**	**5**	**7C**
Drawings-Diagram	**Plate with electrical components - Wiring diagram**	**6**	
Diagram	**Hydraulic diagram**	**7**	

4. DESCRIPTION OF THE MACHINE

4.1 SAFETY STANDARDS COMPLIED WITH DURING THE DESIGN AND CONSTRUCTION OF THE MACHINE

The machine produced by us is in compliance with :

- **2006/42/EEC Machinery Directive .**

The following Standards apply :

- EN ISO12100 2010 Safety of machinery - Basic concepts and general principles for design . Basic terminology and methods .
- EN ISO 16093 2017 Safety of machinery . Basic concepts and general principles for design . Specifications and technical principles .
- EN ISO 13850 2015 Safety of machinery . Emergency stop devices , functional aspects - design principles .
- EN ISO 4413-14 2012 Safety requirements related to systems and components for hydraulics and pneumatic transmissions .
- EN 1037 2008 Safety of machinery . Isolation and energy dissipation . Prevention of unexpected start-up .
- EN 14119 2013 Safety of machinery - Interlocking devices with and without guard – locking . General principles and provisions for design .
- EN 60204-1 2018 Safety of machinery . Electrical equipment of machines. Part 1 : General requirements Sa .
- EN 13857 2008 Safety of machinery . Safety distances to prevent danger zones being reached by the upper limbs .

- **2014/30/EU Directive on electromagnetic compatibility .**

The following Standards apply :

- EN 55014-1 2019 Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus .
- EN 61000-3-2 2018 Electromagnetic compatibility (EMC) -- Part 3-2 : Limits - Limits for harmonic current emissions .
- EN 61000-3-11 2017 Electromagnetic compatibility (EMC) -- Part 3-11 : Limits - Limitation of voltage changes , voltage fluctuations and flicker in public low-voltage supply systems.
- EN 55032 2015 Electromagnetic compatibility of multimedia equipment - Emission requirements .
- EN 61000-4-2 2008 Electromagnetic compatibility (EMC) -- Part 4-2 : Testing and measurement techniques – Electrostatic discharge immunity test
- EN 61000-4-4 2012 Electromagnetic compatibility (EMC) -- Part 4-4 : Testing and measurement techniques - Electrical fast transient/burst immunity test
- EN 61000-4-6 2013 Electromagnetic compatibility (EMC) -- Part 4-6 : Testing and measurement techniques – Immunity to conducted disturbances , induced by radio-frequency fields

- **Low Voltage Directive 2014/35/UE .**

Directive 2003/11/EC Directive 2003/11/EC of the European Parliament and of the Council of 6 February 2003 amending for the 24th time Council Directive 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations (pentabromodiphenyl ether , octabromodiphenyl ether)

Directive 2002/44/EC of the European Parliament and of the Council of 25 June 2002 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (vibration) (sixteenth individual Directive within the meaning of Article 16 (1) of Directive 89/391/EEC)

4.2 DESCRIPTION OF THE MACHINE AND ITS COMPONENTS

The SPECIAL 280 CSO band sawing machine produced by MACC has a sturdy frame made from welded and painted sheet-steel . The upper surface is designed to allow the complete draining away of the cutting fluid . The band holding bow is made of cast-iron and has generous dimensions , providing the cutting unit with the necessary strength and precision . The vice unit is made of cast-iron and clamps the material to be cut securely . The bar-stop device allows the length required to be present and a constant level of performance for repeated cuts . The blade-holding bow is firmly attached to a reduction unit built onto the motor and to the base by means of a joint which allows 60° rotation to the right . This joint also allows the cutting movement to advance manually or by falling .

The coolant pump is fitted to the machine base . The main switch is located on the front panel . The choice of one of the two motor rotation speeds and therefore cutting speed is carried out by the main switch. The front panel is also fitted with an emergency stop button and a START button . The control lever , fitted with an ergonomic hand-grip and activation button with safety release action , reduces fatigue during operation to a minimum . The blade is protected by a guard with interlock which covers the upper area and the hand-wheels and by two adjustable lower guards which protect the operator from ejected shavings and coolant . The machine is supplied with a set of service spanners .

4.3 INTENDED AND UNSUITABLE USES OF THE MACHINE

The SPECIAL 280 CSO band sawing machine has been designed and built to cut bars , structural steel and ferrous metal pipes in accordance with the instructions contained in this manual . Therefore , the cutting of other materials is not permitted : if the above recommendations are not observed , the machine could be damaged and the health and safety of the operator put at risk . Cutting is not permitted , if the bar has not been first locked in the vice .

5. MAIN TECHNICAL DATA

Under no circumstances should the following data be altered , this is in order to protect the correct functioning of the machine and to avoid creating safety risks for the operator .

Three phase power supply	
Motor power	0.75 – 1.1 kW
Motor revolutions	700 - 1420 rpm
Cutting speed	32 - 66 m/1’

Single phase power supply	
Motor power	1.1 kW
Motor revolutions	1380 rpm
Cutting speed	64 m/1’

Electric pump	0.06 kW
Blade size (length x width x thick)	2450 x 27 x 0.9 mm
Cutting thickness	1,2 mm
Cutting angle	60° dx
Material clamping vice max opening	250 mm
Rapid clamping displacement	5 mm
Jaws height	120 mm
Jaws length	160 mm
Bed height	930 mm
Clamping force	3920 N (400 kg)
Coolant tank capacity	12 liters
Machine weight	~2255 N (230 kg)

6. HANDLING AND TRANSPORTATION

For safe handling and transportation use a lift truck for movement indoors also indicated on the DRAW.3 ENCL.2 . Keep the machine in its normal position and avoid turning it upside down . **If the machine is fastened to the pedestal , stability will be greatly reduced and therefore all the necessary measures should be taken to stop the machine from tipping over .**

All handling and transportation operations should be carried out by trained staff .

7. MACHINE INSTALLATION

A. MACHINE CHECK

The machine should be checked to make sure that it has not been damaged during transportation and handling . If the machine appears to have been damaged , contact MACC immediately . Fit all the supplied accessories onto the machine such as the bar stop 118 and the roller arm 143 (DRAW.4 ENCL.2) .

B. FASTENING OF THE MACHINE

The machine will be able to operate in keeping with the technical parameters supplied by MACC if it is positioned correctly and fastened securely to the bench or the factory floor so that vibrations are minimal during operation . Consult drawing 4 SPECIAL 280 CSO Installation plan Encl. 2 .

C. BAND ASSEMBLY

Remove the bow guard 2 by unscrewing the screws 37 the washers 136 and the hand-wheels 124 (DRAW.9-10 ENCL. 5) . Fit the band by inserting it first between the bearings of the blade guide heads and then on the two pulleys , tighten the blade slightly by means of the hand wheel 28 and replace the bow guard . Check that the band is fitted with the correct direction of teeth , as shown in drawing 5 enclosed document 3 . Make sure that the band type (dimensions 2450x27x0.9) and its teeth pitch are suited to the material to be cut .

D. ELECTRICAL CONNECTION TO THE MAINS

Install a differential thermomagnetic switch with characteristics suited to the mains .

Make sure that the power supply voltage corresponds to the voltage on the motor plate . Connect the cable to the power supply line observing the colour codes of the individual wires , pay particular attention to the earth wire . Connect the machine , make sure that the rotation of the circular blade is in the direction shown by the arrow on the guard .

E. CUTTING COOLANT

For the cooling of the circular blade , fill the tank with emulsion oil obtained from a mixture of water and WLADOIL EMULSOL SGA/NF oil with a percentage of 5-7%

8. MACHINE START UP AND OPERATION

8.1 DEVICES AND THEIR LOCATION

(The location of the devices described is shown on the SPECIAL 280 CSO installation plan DRAW.4 ENCL.2)

Code 203 CHANGE OVER SWITCH
Code 96 START-STOP MICROSWITCH : situated inside the handle located at the end of the control lever and has safety release action .
Code 105 ELECTRIC PUMP
Code 117 CUTTING ANGLE DEVICE : to check that cutting inclination is as required
Code 132 LOCKING VICE
Code 118 BAR STOP
Code 94 CONTROL LEVER WITH HANDLE

8.2 TOOLS SUPPLIED

1 Allen wrench size 3
1 Allen wrench size 5
1 Allen wrench size 6
1 Allen wrench size 8
1 Allen wrench size 10

8.3 OPERATION

CHECKS TO CARRY OUT BEFORE EACH CUT

A Tension the band by rotating the hand-wheel 28 to the end of stroke (mechanic stop) .
Remember at the end of the operation to loosen the hand wheel to avoid the slackening of the band .
B Check that the hand indicates the required cutting angle (vice scale) .
C Make sure that the bow and the vice are locked by means of the lever 113 (DRAW.6 ENCL.3) .
D With the motor off , lower the bow and check that at the end of stroke , the band does not touch the counter-vice 115 . If the band does touch , adjust the screw 99 and nut 31 located on the bow .
E Make sure that the piece to be cut is properly secured in the vice .
F Make sure that the cooling liquid is circulating in the machine .

IT IS STRICTLY FORBIDDEN TO USE THE MACHINE WITHOUT CUTTING FLUID

G When starting the motor , make sure that the band rotates in the direction of the arrow shown in DRAW.5 ENCL.3
H To obtain maximum cutting accuracy , the unit must be located the nearest possible to the work piece . Clamp the work-piece with the vice . Release the blade guide arm 60 (DRAW.5 ENCL.3) with clamping lever 17 and move it near the vice jaw so that it doesn't touch it during the cutting operation , then secure it again . When carrying out this operation , make sure that the blade guide guard does not come out of the bow guard leaving a part of the blade exposed .

CUTTING OPERATION

A Before cutting , check that the inclination is the one required . In order to correct or change the inclination , place the bench lever 113 in position C (DRAW.6 ENCL.3) and after correction , move it back to position D .
B Clamp the material to be cut with the hand-wheel 125 after having positioned the clamp near the piece to be cut by lowering the lever 136 from position A to position B allowing a fast displacement (DRAW.6 ENCL.3) with selector 229 in M position . Turn the main switch 203 to the position required , take hold of the handle 95 located at the end of head lever and press the button . The blade will now start turning , position the blade carefully on the piece to be cut . Then increase the pressure in order to accelerate the cutting operation without using excessive force .
C With selector 229 in CSO position . turn the main switch 203 to the position required . After having started the unit by pressing the START push button 208 , the blade starts to rotate . The down stroke of the bow can be adjusted by means of the appropriate regulator . Position the blade carefully on the piece to be cut . Then increase the pressure with the regulator in order to accelerate the cutting operation without using excessive force .
D To make a series of cuts , position the bar stop in correspondence of the size required . Fix it into position by using the hand-wheel 121 (DRAW.7 ENCL.4) .
E To replace the band , carry out the same operations used to assemble the band (chapter 7c) .
F For the choice of blade see table DRAW.1 ENCL.1 .

We strongly discourage the use of blades with ruined or insufficiently sharp cutting edges

8.4 SPECIAL SAFETY CHECKS

A. Before using the machine , check carefully that the safety devices are in good working order , that the mobile parts are not blocked , that no parts are damaged and that all the components are installed correctly and are functioning properly .

B. Make sure , before operating the machine , that the screws of the guards and other protective devices are adequately secured , especially the screws of the bow guard .

C. Check that the safety micro-switches and the emergency button are functioning correctly . Test them during a load less machine cycle .

D. Make sure that the mobile guard does not leave uncovered an angle of more than 5° in order to prevent fingers from entering .

E. Pay attention to environmental conditions . Do not expose the machine to rain ; to not use it in damp environments , position the machine on a clean dry floor that has no oil or grease stains .

F. Before using the machine , the operator should make sure that all tools and service spanners used for maintenance or adjustment have been removed .

8.5 GENERAL SAFETY RULES

A. Wear appropriate clothing . The operator's clothing should not be loose or dangling nor should it have parts which could easily get caught . Sleeves should contain elastic .
Belts , rings or chains should not be worn . Long hair should be kept in a net .
B. Avoid unstable operating positions . Find a safe and evenly balanced position to operate the machine .
C. Keep the work area tidy , untidiness increases the risk of accidents .
D. Do not use the power supply cable to disconnect the plug from the socket . Protect the cable from high temperatures , oil or sharp edges . For outdoor use , only use extension cables which are in line with current regulations .

8.6 MEASURES TO PREVENT RESIDUAL RISKS

A. The removal of guards and tampering with the safety devices is strictly forbidden .
B. Gloves and safety glasses should always be worn .
C. Standard work clothing should be used and kept closed and should not have flapping parts .
D. The machine should not be cleaned with liquids under pressure .
E. In the event of fire , extinguishers should not be used unless they are the powder type . The electric power supply to the machine should always be disconnected in these circumstances .
F. Do not insert foreign bodies into the motor cover and to not supply the machine with voltage by tampering with the safety micro-switches or main switch .
G. Take the necessary precautions to avoid the machine being started by other people during loading , adjustment , piece changing or cleaning .

Safety , Guidance , Notice Labels on the Machine



9. MAINTENANCE AND REPAIRS

9.1 GENERAL SAFETY MEASURES

A. Lockable main switch . Use the padlock in the event of machine failure or replacement of the band . The padlock key should be entrusted to a responsible person .
B. Before carrying out any work on electrical equipment , remove the power supply plug from the control panel (disconnect voltage) .
C. Only use cables to supply power , which have a cross-section suited to the power of the machine .
D. Opening key . The keys of the machine should be kept by authorized personnel . Do not leave the keys for doors which provide access to the hydraulic or electrical parts or keys to lockable switches in easy of reach of unauthorized personnel .
E. Repairs should only be carried out by authorized personnel . Only spare parts made by the original manufacturer should be used , otherwise these could cause damage or injury .

9.2 ROUTINE CHECKS AND MAINTENANCE

FREQUENCY (working hours)	OPERATION
1000 hours	Adjustment blade guide bearings
1000	Lubrication of mobile parts in the piece locking vice (ENI GREASE MU EP 2)
50	Cleaning of the coolant tank and filter check
if necessary	Check functioning of bench lever

9.3 DESCRIPTION OF ROUTINE MAINTENANCE

A. Adjustment of the blade guide bearings

Loosen the screws 69 , rotate the cams 72 , so that the blade guide bushings vertically position the blade in axis (DRAW.5 ENCL.3) . Tighten the dowels 67 until the blade secured . Loosen the dowels 67 slightly (about 1/10 of a turn) and secure the nuts again . The front blade guides must be positioned the nearest possible to the piece to be cut . Check every 3 months the existing tolerance between the blade guides , making sure that it does not exceed the blade thickness of one tenth of a millimeter , so as to avoid inexactnesses in the cut squaring . Periodically check with mounted blade that the blade guide bearings rotate freely .

B. Lubrication of mobile parts of piece locking vice

Remove jaw 137 (DRAW.7 ENCL.4) , withdraw vice 132 completely by lowering the lever 136 . Clean and grease the mobile parts of the counter-vice 115 and vice 132-133 . In case of sliding difficulties or play the clamp guides carry out the following operations : adjust screw 140 .

C. Cleaning of the coolant tank .

The coolant tank can be cleaned by simply removing the crucible 104 (DRAW.4 ENCL.2) . Empty the coolant from the tank and collect the coolant in a container for future disposal . Clean away the shavings and the metallic powder , taking care not to scatter this over the machine especially around the motor and the box containing the electrical equipment . Fill the tank with the amount and liquid stated earlier .

D Checking of bench lever functioning

Check regularly that the rotation release - locking lever is working properly . In the event of the lever not locking correctly , loosen grub screw 122 (DRAW.6 ENCL.3) , tighten nut 114 and fasten grub screw 122 again . Make sure that with the bench lever in position C , arm 109 which supports the bow , can rotate freely .

10.INFORMATION REGARDING ENVIRONMENTAL NOISE

An environmental noise test carried out on the SPECIAL 280 CSO band saw machine , identical to the machine to which these operation instructions refer , has given the following results :

ACOUSTIC RADIATION PRESSURE

1. L_{Aeq} = 83,2 dB (A)
2. L_{peak} = 90,6 dB (the maximum acceptable value is 140 dB) .
3. The level of background noise has no influence = 48.5-54.2 dB (A) .

The considerable data are the result of tests made under the D. lgs. 277/1991 in the implementation of the directives nr. 80/1107/CEE , nr. 82/605/CEE , nr. 84/477/CEE , and 88/642/CEE .

11. LAYING OFF AND DISMANTLING

11.1 LAYING OFF

If the machine is to be laid off or left idle for a long period , the following operations must be carried out :

1. Disconnect the machine from the electricity mains .
2. Empty oil from the gear box and cooling liquid from its tank
3. Clean carefully the machine by getting rid of all traces of grease , especially on the worked parts that must be protected with anti-oxidants .
4. Cover the machine with a sheet , preferably not plastic as it can cause rust due to the humidity condensation .
5. Store the machine in a closed , dust-free place .

11.2 DISMANTLING

If the machine must be definitively dismantled , its components must be sub-divided for the purpose of a possible recycle of the materials and for the environment safety . The following table is given for your guidance :

Steel	Electrical Components	Light alloy	Cast iron	Bronze Copper	Plastic and rubber	Various
Rollers	Motors winding	Gear boxes	Structural parts		Seals	
Spring	Push button and Control system (relais - transformer)	Cylinder			Handle with push-button	
Flange, pin					Hand-wheel	
Base	Electronic panel					
Tank						
Plate with electrical components						
Guard						

Used oil and materials must be disposed of according to 87/101/EEC Directives and to country specific regulations .

The disposal of electrical components is provided for by European Directives UE 2015/863 .

12. LIST OF SPARE PARTS

POS.	DESCRIPTION	CODE	Q.TY
1	Bow	006-A/35	1
2	Bow guard	084/35	1
3	HH screw M12x25 DIN-933	239/95	1+1
4	Washer as drawing ø45x12,5x6	040/06	2
5	Snap ring ø72 I DIN-472	426/95	1
6	Cylinder bracket bushing	070/38	1+1
7	Idle pulley spacer	022/35	1
8	Bearing 6207 2RS	103/32	2
9	Idle pulley	009/35	1
10	Blade tightener pin	037/35	1
11	Grub screw M6x12 DIN-913	052/95	2
12	HSHC screw M8x16 DIN-912	151/95	6
13	Blade tightener guide plate	046/32	2
14	HSHC screw M4x30 DIN-912	126/95	2
15	Blade tightener screw	039/32	1
16	Washer ø10 DIN-125/A	005/95	1
17	Clamping lever M10x40	061/35	1
18	Mobile saw-blade guide fastening plate	018/35	1
19	Rear guard	042/38	1
20	Micro ERSCE E 100 01 S5I	030/90	1
21	Bearing vice flange	020/31	1
22	End stroke plate	083/35	1
23	Blade tightener bush	041/38	1
24	Casing AXK 20 35	109/32	1
25	Thrust bearing AS 20 35	108/32	2
26	Belleville washer 40x20,4x1,5 DIN-2093	458/95	17
27	Spring pin ø8x36 DIN-1481	330/95	1
28	Blade tightener hand-wheel	058/35	1
29	Eye tie rod M12x50	035/38	2
30	Cover plate	085/35	1
31	Medium nut M8 DIN-934	014/95	1+1
32	Band M42 2450x27x0.9 Z5/8	MAR2450270958	1
33	Rotating pin nut	027/38	1
34	Push micro plate	072/35	1
35	HH screw M12x25 DIN-933	239/95	1+1
36			
37	HSHC screw M6x12 DIN-912	137/95	2+2
38	Reduction unit MV 63 FC 1/19	021/38	1
39	Motor M90L V400/50 8/4P HP1/1,5	122/80	1
40			
41			
42	HH screw M6x25 DIN-933	142/95	3
43	Washer ø6 UNI-7064	611/95	3
44	Washer ø6 DIN-125/A	003/95	2+2
45	Medium nut M6 DIN-934	011/95	3
46	Micro-switch E-100-00 BI	023/90	1
47	HH screw M8x14 DIN-933	211/95	1+1
48	Bearing 6208 2RS	016/38	1
49	Washer ø10 DIN-125/A	005/95	4
50	Medium nut M10 DIN-934	017/95	4
51	HSHC screw M8x14 DIN-912	153/95	1+1
52	HH screw M10x25 DIN-933	225/95	4
53	Micro-switch E-100-00-AI	022/90	1
54	Key 10x8x20 DIN-6885A	377/95	1
55	Motor pulley	008/35	1
56	Washer	053/31	1
57	HSHC screw M8x16 DIN-912	155/95	2
58	HSFHC screw M8x20 DIN-7991	259/95	2
59	HSHC screw M8x25 DIN-912	158/95	3
60	Mobile blade guide rod	023/35	1
61	HSFHC screw M8x20 DIN-7991	259/95	1
62			
63	Front blade-guide guard	071/38	1
64	HH screw M8x25 DIN-933	214/95	4
65	Blade guide tap	030/96	1
66	Front blade guide	026/35	1
67	Grub screw M8x16 DIN-913	056/95	1+1

68	Blade guide plate	044/35	2+2
69	HSHC screw M6x25 DIN-912	128/95	2
70	Washer ø6 DIN-125/A	003/95	1+1
71	Bearing 608 2RS	055/35	1+1
72	Blade guide eccentric bush	027/35	1+1
73	Micro-switch holder	015/34	1
74	Rear blade guide	025/35	1
75	HSHC screw M10x20 DIN-912	175/95	2
76			
77	Rotation pin	021/34	1
78	Bearing 32008 XA	072/20	2
79	Nut M12 DIN-936	019/95	1
80	HH screw M10x120 DIN-933	237/95	1
81	Stop micro-switch bush	047/38	1
82	Cover box	202/34	1
83	Seeger ring ø40 DIN-471	412/95	2
84	Control box	201/34	2
85	Control box support bracket	105/34	1
86	Positioning pin	002-B/35	1
87	Sphere ø30 F.M. 10	082/14	1
88	Anchor spring bracket	014/34	1
89	Return spring	019/33	1
90	Spring pin	068/38	1
91	HSFHC screw M6x8 DIN-7991	252/95	2
92	Fixed blade-guide guard	071-D/38	1
93	Fixing counter-vice bracket	011/34	1
94	Knob rod	035/32	1
95	Knob	146/05	1
96	Micro-switch	028/90	1
97	Anti-grease ring	020/35	1
98	Rear movable blade-guide guard	071-A/38	1
99	HH screw M8x30 DIN-933	215/95	1
100	Hub flange	003/34	1
101	Base	001/34	1
102	Washer ø6 DIN-125/A	003/95	2
103	Hub	200/34	1
104	Crucible	002-A/34	1
105	Motor pump SC/85	090/90	1
106	Regulator box	099/14	1
107	Bow support	005/34	1
108	Cylinder bracket	061/38	1
109	Rotating arm	004/34	1
110	HSHC screw M8x20 DIN-912	157/95	2
111	Counter vice pin	010/34	1
112	Hinge + pin	041/39	1
113	Bench lever	062/32	1
114	Bench lever nut	027/04	1
115	Counter-vice	006/34	1
116	Bar stop rod	031/05	1
117	Cutting angle device	A	1
118	Bar stop	004/05	1
119	Nut M16 DIN-936	025/95	1
120			
121	Hand-wheel ø40 4L M8x20	077/25	2
122	Hexagon socket grub screw M8x10 DIN-914	085/95	1+1
123	HSHC screw M8x25 DIN-912	158/95	2+2
124	Hand-wheel ø30 4L M6x10	062/35	2
125	Vice hand-wheel	056/35	1
126	Hex. socket grub screw M6x10 DIN-914	081/95	1+4+4
127	Vice screw	067/35	1
128	Washer ø8 DIN-125/A	004/95	1+1+4
129	Vice spring	021/31	1
130	Fifth wheel AS 30 47	061/31	2
131	Cage AxK 30 47	060/31	1
132	Vice	005/33	1
133	Bush	018/34-BIS	1
134	Oiler ø6	490/95	1
135	Vice lever	007/31	1
136	Hydraulic cylinder CSO	017/34	1
137	Vice jaw	009/34	1


138	HH screw M8x40 DIN-933	216/95	1
139			
140	HSHC screw M6x85 DIN-912	154/95	1
141			
142	Roller	076/32	1
143	Roller arm	075/35	1
144	Counter-vice big jaw	007/34	1
145	Counter-vice small jaw	008/34	1
200	Plate with electrical components	204/34	1
201	Control panel	206/34	1
202	Fuse 10x38 gG 2A	203/90	1
203	Change over switch	018/90	1
204	HSHC screw M4x6 DIN-912	120/95	2+2
205	Transformer 30VA 0-230-400V 0-24V	045/90	1
206	Fitting Pg 11	214/90	1
207	Fitting Pg 13,5	215/90	4
208	On switch	086/90	1
209	HSHC screw M4x12 DIN-912	122/95	3
210	OMEGA raceway (cm.15)	046/90	1
211	OMEGA raceway (cm.17)	047/90	1
212	Terminal CABUR CBD.2	222/90	21
213	Earth terminal TE.6/0	223/90	2
214	Screw TBEI M4x6 ISO-7380	280/95	2+2
215	Remote controlled switch	032/90	1
216	HSHC screw M5x8 DIN-912	128/95	3
217	Earth connection bar with 5 holes	050/90	1
218	Thermal relay LR2-D1308/10/12	053/90	1
219	Fuse block PCH 1x38	093/90	1
220	Fuse block PCH 2x38	094/90	1
221	Fuse 10x38 gG 1A	202/90	2
222	Electrical cable 2X1	003/77	1
223	Screw TCTCR M2,9x13 DIN-7981	294/95	6
224			
225	HSFHC screw M4x8 DIN-7991	255/95	1
226	Emergency button	085/90	1
227	Green warning light 24V	267/90	1
228	Fitting Pg 9	213/90	7
229	Selector XB2-BD21	100/90	1
230	Switch VEMER CA0120003807+G595	002/90	1
231	Fuse 10x38 gG 10A	206/90	3
232	Fuse block PCH 10x38	092/90	1

CAPACITA' DI TAGLIO - Special 280 M-CSO


CAPACITA' DI TAGLIO CUTTING CAPACITY - CAPACITE DE COUPE SCHNITTKAPAZITAET - CAPACIDAD DE CORTE	○	□	a b axb
0°	220	215	155 x 250
45°	160	150	110 x 160
60°	100	85	80 x 95

SCELTA DELLA LAMA

SCELTA DELLA LAMA
SELECTION OF BLADE
CHOIX DE LA LAME
WAHL DES SAEGEBLATTS
SELECCION DE LA HOJA



L mm	Zx1"	Zx1" Zx1"
≦40	8	6/10
>30<80	6	5/8
>60<90	4	4/6
≦100	3	3/4



S mm	Zx1"	Zx1" Zx1"
≦1,5	14	-
>1<2	10	10/14
>2<4	8	8/12
>4<8	6	6/10
>6<12	6	5/8
≦12	4	4/6


Allegato / Encl. 1 - Dis. / Draw. 1

Velocità di taglio La macchina è dotata di due velocità di taglio	32-66 m/1'
Cutting machine The machine is equipped with two cutting speeds	32-66 m/1'
Vitesse de coupe La machine est dotée de deux vitesses de coupe	32-66 m/1'
Schnittgeschwindigkeit Die maschine ist mit zwei Schnittgeschwindigkeiten ausgetattet	32-66 m/1'
Velocidad de corte La maquina esta dotata de dos velocidades de corte	32-66 m/1'
Materiale Material Materiel Material Material	Velocità di taglio m/1' Cutting machine m/1' Vitesse de coupe m/1' Schnittgeschwindigkeit m/1' Velocidad de corte m/1'
Acciai da costruzione Fe37+Fe42 Structural steel Fe37+Fe42 Aciers de costruction Fe37+Fe42 Baustahl Fe37+Fe42 Acero de costruccion Fe37+Fe42	Pieni Solid Pleins Volles Material Pies 66
	Profilati Structural steel Profilés Profile Perfiles 66
Acciai da costruzione Fe50+Fe70 Structural steel Fe50+Fe70 Aciers de costruction Fe50+Fe70 Baustahl Fe50+Fe70 Acero de costruccion Fe50+Fe70	66
Acciai al carbonio C40+C60 Carbon steel C40+C60 Aciers au carbone C40+C60 Kohlenstoffstahl C40+C60 Acero de carbono C40+C60	66
Acciai legati Alloyed steel Aciers allié Legierter Stahl Acero aleado	32
Acciai inox Stainless steel Aciers inoxydables Rostfreier Stahl Acero inoxidable	32
Ghisa grigia Grey cast iron Fonte grise Grauguß Fundiciòn gris	66
Leghe d'alluminio Alluminium alloys Allieges d'aluminium Legierungen aus Aluminium Aleaciòn de Aluminio	66
Bronzi Bronze Bronze Bronze Bronces	66

Allegato / Encl. 1 - Dis. / Draw. 2

MOVIMENTAZIONE E TRASPORTO


Handling and transportation
Manutention et transport
Handhabung und Transport
Movilización y transporte




Allegato / Encl. 2 - Dis. / Draw. 3


DIMENSIONI D'INGOMBRO ED INSTALLAZIONE


Overall dimensions and installation
Dimensions hors-tout et installation
Aussenabmessungen und installation
Dimensiones máximas extremas e instalación




Allegato / Encl. 2 - Dis. / Draw. 4












Allegato / Encl. 3 - Dis. / Draw. 5





Allegato / Encl. 3 - Dis. / Draw. 6







Allegato / Encl. 4 - Dis. / Draw. 7










Allegato / Encl. 4 - Dis. / Draw. 8





Allegato / Encl. 5 - Dis. / Draw. 9
























Allegato / Encl. 5 - Dis. / Draw. 10








Allegato / Encl. 6 - Dis. / Draw. 11



SCHEMA IDRAULICO

IDRAULIC DIAGRAM




	ITALIANO	ENGLISH	DEUTSCH
FR1	RELE' TERMICO MOTORE POMPA OLIO	THERMAL RELAY OIL PUMP MOTOR	THERMISCHES RELAIS OIL PUMPE MOTOR
FR2	RELE' TERMICO MOTORE LAMA	THERMAL RELAY BLADE MOTOR	THERMISCHES RELAIS SÄGEBLATTMOTOR
FR3	RELE' TERMICO MOTORE REFRIGERANTE	THERMAL RELAY COOLANT MOTOR	THERMISCHES RELAIS ÜHLMITTELMOTOR
FR4	RELE' TERMICO MOTORE ESTRATTORE TRUCIOLI	RELAY THERMAL CHIPS EXTRACTOR MOTOR	THERMISCHES RELAIS CHIP EXTRACTORMOTOR
FR5	RELE' TERMICO MOTORE GUIDA PEZZO	THERMAL RELAY GUIDA-PIECE MOTOR	THERMISCHES RELAIS Motor Führungsstück
FTC	FOTOCELLULA PRESENZA MATERIALE	MATERIAL PRESENCE PHOTOELECTRIC CELL	Photozelle Werkstoff Anwesenheit.
FU1	FUSIBILI PROTEZIONE TRASFORMATORE	FUSE TRANSFORMER PROTECTION	SICHERUNG TRAFO SCHUTZ
FU2	FUSIBILI PROTEZIONE MOTORI	FUSE MOTOR PROTECTION	SICHERUNG MOTOR SCHUTZ
FU3	FUSIBILI PROTEZIONE POMPA REFRIGERANTE	FUSE COOLANT PUMP PROTECTION	SICHERUNG KÜHLMITTELPOMPE SCHUTZ
FU4	FUSIBILI PROTEZIONE ALIMENTATORE	FUSE FEEDER PROTECTION	SICHERUNG ZUFÜHRER SCHUTZ
FU5	FUSIBILI PROTEZIONE 24 V dc	FUSE 24 V dc PROTECTION	SICHERUNG 24 V dc SCHUTZ
FU6	FUSIBILI PROTEZIONE 24 V ac	FUSE 24 V ac PROTECTION	SICHERUNG 24 V ac SCHUTZ
FU7	FUSIBILE PROTEZIONE MOTORE INVERTER	FUSE INVERTER PROTECTION	GESCHWINDIGKEITUMRICHTER SICHERUNGSDRAHT
G	GALLEGGIANTE	FLOAT	SCHWIMMER
H1	SPIA PRESENZA LINEA	SPY LINE PRESENCE	LINE PRÄSENZ LAMPE
H2	SPIA LAMA IN TENSIONE	SPY BLADE IN TENSION	BLATT TENSION LAMPE
H3	SPIA START CICLO	SPY CYCLE START	ZYKLUS START LAMPE
K	TELERUTTORE TERMORESISTENZA	THERMO-RESISTANCE CONTROL SWITCH	KONTAKTGEBER WIDERSTANDSTHERMOMETER
KM0	TELERUTTORE ALIMENT. INVERTER	INVERTER FEEDING CONTROL SWITCH	Fernschalter Frequenzumrichter Versorgung
KM1	TELERUTTORE MOTORE POMPA OLIO	OIL PUMP MOTOR REMOTE CONTROL SWITCH	KONTAKTGEBER ZENTRALHYDRAULIK MOTOR
KM2	TELERUTTORE MOTORE LAMA	BLADE MOTOR REMOTE CONTROL SWITCH	KONTAKTGEBER SÄGEBLATTMOTOR
KM3	TELERUTTORE POMPA REFRIGERANTE	COOLANT PUMP REMOTE CONTROL SWITCH	KONTAKTGEBER KÜHLMITTELPUMPE
KM4	TELERUTTORE ESTRATTORE TRUCIOLI (COCLEA)	CHIP EXTRACTOR CONTROL SWITCH	KONTAKTGEBER SPÄNE AUSZIEHER
KM5	TELERUTTORE MOTORE GUIDA PEZZO	THERMAL RELAY GUIDA-PIECE MOTOR CONTROL SWITCH	KONTAKTGEBER Motor Führungsstück
KM6	TELERUTTORE POMPA RECUPERO REFRIGERANTE	COOLANT RECYCLE PUMP THERMAL RELAY	KONTAKTGEBER KUEHLMITELPUMPE
M1	MOTORE POMPA OLIO	OIL PUMP MOTOR	ZENTRALHYDRAULIKMOTOR
M2	MOTORE LAMA	BLADE MOTOR	SÄGEBLATTMOTOR
M3	MOTORE POMPA REFRIGERANTE	COOLANT PUMP MOTOR	KÜHLMITTELPUMPE MOTOR
M4	MOTORE ESTRATTORE TRUCIOLI	CHIP EXTRACTOR MOTOR	SPAENEAUSLASSVORRICHTUNG MOTOR
M5	MOTORE ROTAZIONE TESTA	SAWHEAD ROTATION MOTOR	DREHUNGS KOPF MOTOR
M50	MOTORE GUIDA PEZZO	GUIDA-PIECE MOTOR	FÜHRUNGSSTÜCK MOTOR

M6	MOTORE AVANZAMENTO MATERIALE	MATERIAL FEEDING OTOR	VORSCHUBMATERIAL MOTOR
P1	POTENZIOMETRO POSIZIONAMENTO LAMA	BLADE POSITIONING POTENTIOMETER	SÄGEBLATT-STENUNG POTENZIOMETER
P2	POTENZIOMETRO VELOCITA' LAMA	BLADE SPEED POTENTIOMETER	SÄGEBLATT-GESCHWINDIGKEIT POTENZIOMETER
PX1	SENSORE ROTAZIONE LAMA	BLADE ROTATION SENSOR	BLATT UMDREHUNGSSENSOR
QS1	INTERRUTTORE GENERALE	MAIN ON / OFF SWITCH	HAUPTSCHALTER
QS2	INTERRUTTORE / COMMUTATORE DI VELOCITA'	SWITCH / SPEED CHANGE OVERSWITCH	SCHALTER / GESCHWINDIGKEIT UMSCHALTER
QS3	INTERRUTTORE POMPA REFRIGERANTE	COOLANT PUMP SWITCH	KÜHLMITTELPUMPE SCHALTER
R	RELE' COMANDO MARCIA ROTAZIONE LAMA	ROTATING BLADE COMMAND RELAY	SÄGEBLATT UMDREHUNG POTENZIOMETER
R1	RELE' COMANDO TELERUTTORE POMPA OLIO	OIL PUMP REMOTE CONTROL SWITCH COMMAND RELAY	RELAIS OIL PUMPE FERNSCHALTER
R10	RELE' PRESSINO ON	VERTICAL VICE RELAY	SENKRECHT SCHRAUBSTOCK RELE
R2	RELE' COMANDO TELERUTTORE LAMA	BLADE REMOTE CONTROL SWITCH COMMAND RELAY	RELAIS BLATT FERNSCHALTER
R5	RELE' COMANDO MICROLUBRIFICAZIONE	MICROLUBRICATION COMMAND RELAY	MIKROSPRÜHEINRICHTUNGSTEUER RELAIS
RT	RELE' TEMPORIZZATORE	TIMER RELAY	ZEITGEBER RELE
RX	RELE' COMANDO TERMOSTATO	THERMOSTAT COMMAND RELAY	THERMOSTATSTEUER RELAIS
RYV5	RELE' DISCESA LAMA	BADE DESCENT RELAY	SAEGEBLATT ABSTIG RELE
S	SELETTORE FUNZIONE	FUNCTION SELECTOR	FUNKTION WÄHLER
S10	SELETTORE PRESSINO ON	VERTICAL VICE ON CHANGEOVER SWITCH	GESCHWINDIGKEITUMRICHTER WAEHLER ON
S4	SELETTORE CAMBIO LAMA	BLADE RELACEMENT CHANGEOVER SWITCH	SAEGEBLATT WAEHLSCHALTER
SB1	PULSANTE DI ARRESTO EMERGENZA	EMERGENCY PUSH BUTTON	NOT AUS TASTER
SB11	PULSANTE DETENSIONAMENTO LAMA	BLADE DETENSIONING BUTTON	SAEGEBLATT ENSPANNSCHALTER
SB12	PULSANTE TENSIONAMENTO LAMA	BLADE TENSIONING BUTTON	SAEGEBLAT SPANNSCHALTER
SB2	PULSANTE START CICLO	CYCLE START BUTTON	ZYKLUS START TASTER
SB3	PUSANTE DI RESET	RESET BUTTON	RESETTASTER
SB4	PULSANTE CHIUSURA MORSA	LOCK VICE BUTTON	SPANNSOCH SCHLIEß TASTER
SB5	PULSANTE APERTURA MORSA	OPEN VICE BUTTON	SPANNSTOCK ÖFFNUNG TASTER
SB6	PULSANTE DI SALITA	BUTTON UP	OBEN TASTER
SB7	PULSANTE DI DISCESA	BUTTON DOWN	HINTEN TASTER
SB8	PULSANTE REFRIGERANTE “ON”	REFRIGERANTE BUTTON “ON”	KÜHLUNG EIN TASTER
SB9	PULSANTE MEMORY	MEMORY BUTTON	MEMORY TASTER
SB90	PULSANTE DI SBLOCCO	RELEASE BUTTON	AUSLOESER TASTE
SQ02	MICROINTERRUTTORE CARTER APERTO SX	COVER OPEN MICROSWITCH	SCHUTZ GEÖFFNET ENDSCHALTER
SQ1	MICROINTERRUTTORE ROTTURA LAMA	MICROSWITCH BLADE FAILURE	ENDSCHALTER BLATT GEBROCHEN

SQ10	MICROINTERRUTTORE START A PEDALE	PEDAL MICROSWITCH START	PEDALS MIKROSCHALTER
SQ11	MICROINTERRUTTORE CHIUSURA MORSA A PEDALE	PEDAL VICE CLOSING MICROSWITCH	FuβSCHALTER SPENNSTOCK SCHLIEβEN MIKROSCHALTER
SQ15	FINECORSA GUIDA PEZZO AVANTI	MICROSWITCH GUIDE-PIECE FORWARD	ENDSCHALTER FÜHRUNGSSTÜCK NACH VORNE
SQ16	FINECORSA GUIDA PEZZO INDIETRO	MICROSWITCH GUIDE-PIECE BACKWARD	ENDSCHALTER FÜHRUNGSSTÜCK NACH HINTEN
SQ18	FINECORSA SOLLEVATORE ALTO	MICROSWITCH LIFT UP POSITION	HEBEWERK NACH OBEN ENDSCHALTER
SQ2	MICROINTERRUTTORE CARTER APERTO	MICROSWITCH PROTECTION CASE	ENDSCHALTER SCHUTZGEHÄUSE
SQ20	PRESSOSTATO CHIUSURA MORSA	VICE PRESSURE SWITCH	SPANNDRUCK TASTE
SQ3	FINECORSA CARRO AVANTI	MICROSWITCH CARRIAGE FORWARD	ENDSCHALTER WAGEN VORNE
SQ30	FINECORSA ROTAZIONE -45°	MICROSWITCH -45° ROTATION	-45° UMDREHUNG ENDSCHALTER
SQ4	FINECORSA CARRO INDIETRO	MICROSWITCH CARRIAGE BACK	ENDSCHALTER WAGEN ZURÜCK
SQ5	FINECORSA TESTA ALTA	MICROSWITCH HEAD / BOW UP	ENDSCHALTER BÜGEL NACH OBEN
SQ6	FINECORSA TESTA BASSA	MICROSWITCH HEAD / BOW DOWN	ENDSCHALTER BÜGEL NACH UNTEN
SQ7	MICROINTERRUTTORE FINE MATERIALE	MICROSWITCH BAR END	ENDSCHALTER STANGENENDE
SQ70	PROSSIMITI PRESENZA PEZZO	MICROSWITCH PIECE PRESENCE	STÜCKANWESENDHEIT ENDSCHALTER
SQ8	MICROINTERRUTTORE MANIGLIONE	MICROSWITCH HANDLE	ENDSCHALTER GRIFF
SQ9	MICROINTERRUTTORE START MANUALE	MICROSWITCH MANUAL START	ENDCSHALTER MANUELL START
T	TEMPORIZZATORE	TIMER	ZEITGEBER
TC1	TRASFORMATORE	TRANSFORMER	TRANSFORMATOR
TR	TERMOSTATO	THERMOSTAT	THERMOSTAT
TR	TERMORESISTENZA	THERMO-RESISTANCE	THERMO-WIDERSTAND
YV1	ELETTROVALVOLA CARRO AVANTI LENTO	CARRIAGE SLOW FORWARD MOTION SOLENOID VALVE	ELEKTROVENTIL WAGEN LANGSAM VORNE
YV10	ELETTROVALVOLA SBLOCCAGGIO MANUALE	MANUAL UNLOCKING SOLENOID VALVE	ELEKTROVENTIL MANUELL AUFHEBUNG
YV11	ELETTROVALVOLA DETENSIONAMENTO LAMA	UNTIGHTNING BLADE SOLENOID VALVE	SAEGEBLATT ENTSPANNUNG MAGNETVENTIL
YV11	ELETTROVALVOLA DETENSIONAMENTO LAMA	BLADE DETENSIONING SOLENOID VALVE	ELETRISCHESVETIL SAEGEBLATT ENSPANNUNG
YV12	ELETTROVALVOLA TENSIONAMENTO LAMA	TIGHTNING BLADE SOLENOID VALVE	SAEGEBLATT SPANNUNG MAGNETVENTIL
YV12	ELETTROVALVOLA TENSIONAMENTO LAMA	BLADE TENSIONING SOLENOID VALVE	ELETRISCHESVENTIL SAEGEBLATT SPANNUNG
YV15	ELETTROVALVOLA SOLLEVATORE CARICATORE	LOADER LIFT SOLENOID VALVE	LADEMAGAZIN HEBEWERK ELEKTROVENTIL
YV16	ELETTROVALVOLA MORSA CARICATORE	LOADER VICE SOLENIOID VALVE	LADEMAGAZINSPANNSTOCK ELEKTROVENTIL
YV18	ELETTROVALVOLA GIUDA PEZZO AVANTI	GUIDE-PIECE FORWARD VALVE	ELEKTROVENTIL ZAUN NACH VORNE
YV19	ELETTROVALVOLA GUIDA PEZZO INDIETRO	GUIDE-PIECE BACKWARD VALVE	ELEKTROVENTIL HINTEREN ZAUN
YV2	ELETTROVALVOLA CARRO INDIETRO LENTO	CARRIAGE SLOW BACK MOTION SOLENOID VALVE	ELEKTROVENTIL WAGEN LANGSAM ZURÜCK
YV20	SBLOCCAGGIO ROTAZIONE	ROTATION UNLOCK	UMDREHUNG LOSMACHEN

YV3	ELETTROVALVOLA MORSA MOBILE	MOVABLE VICE SOLENOID VALVE	ELEKTROVENTIL BEWEGLICHER SPANNSTOCK
YV30	ELETTROVALVOLA MORSA MOBILE CHIUDE	CLOSE MOVABLE VICE VALVE	BEW. SPANNSTOCK SCHLIEß ELEKTROVENTIL
YV30P	ELETTROVALVOLA PRESSINO CARRO	CARRIAGE VICE SOLENOID VALVE	ELETRISCHESVENTIL SCHRAUBSTOCK VORSCHUBWAGEN
YV31	ELETTROVALVOLA RUOTA ARCO LENTO	SLOW BOW ROTATION SOLENOID VALVE	LANGSAM SÄGEARMUMDREHUNG ELEKTROVENTIL
YV37	ELETTROVALVOLA RUOTA DX	ROTATION LEFTWARDS SOLENOID VALVE	UMDREHUNG LINKS ELEKTROVENTIL
YV38	ELETTROVALVOLA RUOTA SX	ROTATION RIGHTWARDS SOLENOID VALVE	UMDREHUNG RECHTS ELEKTROVENTIL
YV4	ELETTROVALVOLA SALITA	UP STROKE SOLENOID VALVE	ELEKTROVENTIL ANSTIEG
YV5	ELETTROVALVOLA DISCESA	DOWN STROKE SOLENOID VALVE	ELEKTROVENTIL ABSTIEG
YV50	ELETTROVALVOLA DISCESA LAMA RAPIDA	QUICK LOWERING SOLENOID VALVE	SCHNELL ELEKTROVENTIL ABSTIEG
YV6	ELETTROVALVOLA APERTURA MORSA FISSA	FIXED VICE OPENING SOLENOID VALVE	ELEKTROVENTIL FESTER SPANNSTOCK ÖFFNUNG
YV60	ELETTROVALVOLA CHIUSURA MORSA FISSA	FIXED VICE CLOSING SOLENOID VALVE	ELEKTROVENTIL FESTER SPANNSTOCK SCHLIESSEN
YV60P	ELETTROVALVOLA PRESSINO FISSO	FIXED VICESOLENOID VALVE	ELETRISCHESVENTIL FESTSCHRAUBSTOCK
YV61	ELETTROVALVOLA SPAZZOLA	BRUSH VALVE	BÜRSTE ELEKTROVENTIL
YV62	ELETTROVALVOLA ATTIVAZIONE 2a POMPA OLIO	SECOND OIL PUMP	ZWEITE ÖLPUMPE EIN ELEKTROVENTIL
YV7	ELETTROVALVOLA CARRO AVANTI	CARRIAGE FORWARD SOLENOID VALVE	ELEKTROVENTIL WAGEN VORNE
YV70	ELETTROVALVOLA SPAZZOLA	BRUSH SOLENOID VALVE	BUERSTE MAGNETVENTIL
YV8	ELETTROVALVOLA CARRO INDIETRO	CARRIAGE BACK SOLENOID VALVE	ELEKTROVENTIL WAGEN ZURÜCK
YV9	ELETTROVALVOLA BLOCCO	MANUAL LOCKING SOLENOID VALVE	ELEKTROVENTIL BLOCK
YV90	ELETTROVALVOLA MICROLUBRIFICAZIONE	MICROLUBRICATION SOLENOID	MIKROSPRÜHEINRICHTUNG ELEKTROVENTIL



V400 / 50 3F

Rev.	Modificato	C./Appr.	Data	Descrizione

DENOMINAZIONE: Schema Elettrico

Data 13/04/2015

Firma *Franco Luciano*

Contr./Appr.

MACC Schio

Modello: /


Macchina: SEGATRICE 280 CSO/M

N° Schema 145/SS

Revisione

Foglio 1 di 1

V230 / 50 1F



Rev.	Modificato	C./Appr.	Data	Descrizione

DENOMINAZIONE: **Schema Elettrico**

Data 26/10/2015

Firma *Andrea Scremin*

Contr./Appr.

MACC Schio

Modello: /

Macchina: **SEGATRICE 280 CSO/M**

N° Schema 145/SS

Revisione

Foglio 1 di 1

CONTROLLATO IL:	10/03/15
DA:	
REV.:	01